


# Blackhawk MVDS Composite Cable Assembly BH-031



Blackhawk BH-031 MVDS composite cable assemblies provide high quality cables within a single jacket for ease and neatness of CCTV installations. Two 18 ga. TFFN wires provide power and a dual twisted pair with individual shields and common drain provides data connection to the detector for RS-232 or RS-485.

With a rugged UV resistant PVC jacket, the composite cable provides an ideal solution for most outdoor and indoor CCTV applications, including camera lowering devices.

<b>Outer Jacket:</b>		<b>Power:</b>	
Material	UV Resistant PVC	No. of wires	2
Nom. Jacket Thickness	.09"	AWG size	18 AWG
Tensile Strength	2,650 psi	Type	TFFN
No Lead Content		Strands	26
		Voltage	600V
		High Temp	+90 Celsius
		Jacket	Nylon over PVC
		<b>Low Speed Data:</b>	
		Data Cable:	
		No. of Pairs	2
		AWG Size	22 AWG
		Each pair individually shielded	Yes
		Both pairs common shielded	Yes
		Common shield drain wire	Yes
		Nom. Capacitance	26 pF/FT

For ordering information contact: Blackhawk Enterprises at (850) 668-5293 or e-mail to [blhawk99@aol.com](mailto:blhawk99@aol.com)